





Comfort and productivity

- A comfortable working environment has been created in the cabin so long working days are no problem. The steering column is fully adjustable and all necessary information can easily be read from a central display;
- The hydrostatic 4-wheel drive with automotive control (Rexroth) and 100% switchable lock on both, 16-tons, axles always provides enough grip, a lot of pulling force a smooth movement;
- The hydraulics can be extended to a servo-controlled version. A high flow version is also available, which can deliver 31.7 GPM to the chosen attachment;
- The G5000 can be configured completely according to your wishes. Depending on your work you choose a Z-bar, X-TRA or TELE version with correct options.



	G5000 Z-BAR	G5000 X-TRA	G5000 TELE
Engine	75 hp (Kubota)	75 hp (Kubota)	75 hp (Kubota)
Service weight	9,920 lbs.	9,700 lbs.	10,140 lbs.
Lifting height	137.8 in.	112.2 in.	171.3 in.
Tipping load	7,360 lbs.	9,850 lbs.	see table
Working hydraulics	21.1 GPM (optional: 31.7 GPM)	21.1 GPM (optional: 31.7 GPM)	21.1 GPM (optional: 31.7 GPM)
Max. speed	12.4 mp/h (optional: 21.6 mp/h)	12.4 mp/h (optional: 21.6 mp/h)	12.4 mp/h (optional: 21.6 mp/h)








TECHNICAL SPECIFICATIONS

Dimensions

	G5000 Z-BAR	G5000 X-TRA	G5000 TELE
Α	80.5 in.	80.5 in.	80.5 in.
В	164 in.	163.9 in.	175.4 in.
С	196.9 in.	196.6 in.	209.1 in.
D	27.8 in.	27.8 in.	27.8 in.
E	7.8 in.	7.8 in.	7.8 in.
F	27.6 in.	27.6 in.	27.6 in.
G	63 in.	63 in.	63 in.
Н	99.3 in.	99.3 in.	99.3 in.
I	100.5 in.	100.5 in.	100.5 in.
J	72.4 in.	69.8 in.	75 in.
K	100.4 in.	75.6 in.	133.9 in.
L	137.8 in.	112.2 in.	171.3 in.
M	167.3 in.	141.7 in.	200.8 in.
N	45°	45°	41°
0	54°	43°	-
Р	46°	46°	41°
Q	29°	29°	29°
R	Ø 41.3 in.	Ø 41.3 in.	Ø 41.3 in.
1 A	141.3 in.	141.3 in.	147.2 in.
1B	125.6 in.	125.6 in.	125.6 in.
1C	68.7 in.	68.7 in.	68.7 in.
1D	57.5 in.	57.5 in.	57.5 in.







Tipping loads

	G5000 Z-BAR	G5000 X-TRA
S	7,363 lbs	9,855 lbs
T	7,079 lbs	8,490 lbs
U	5,512 lbs	6,321 lbs
V	4,383 lbs	5,033 lbs
W	10,048 lbs	10,699 lbs
X	6,991 lbs	7,445 lbs
Υ	5,176 lbs	5,512 lbs

G5000 TELE

177.17

157.48

137.80

118.11

98.43

78.74

59.06

37.37

19.89

98.99

98.99

98.90

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

10.60

TOBROCO-GIANT reserves the right to make changes in specifications at any time without notice or obligation.



TOBROCO-GIANT USA

725 Ida Street, Cedar Falls IA 50613, USA Tel.: +1 319-449-3677 Fax.: +1 319-449-3738

Internet: www.tobroco-giant.us E-Mail: info@tobroco-giant.us