

# G2300HD SERIES COMPACT WHEEL LOADER



## POPULAR OPTIONS

Pro-Inching  
Extra Constant Flow Pump  
Cab with Heat - Heated Air-ride Seat  
Variety of Tire Options

## G2300HD SERIES QUICK SPECS

|                                | G2300HD                                 | G2300HD X-TRA                           |
|--------------------------------|-----------------------------------------|-----------------------------------------|
| ENGINE                         | KUBOTA, 25 HP                           | KUBOTA, 25 HP                           |
| SERVICE WEIGHT                 | 5,070 LBS                               | 5,181 LBS                               |
| LIFTING HEIGHT                 | 111.4 IN                                | 96.5 IN                                 |
| LIFT CAPACITY<br>(PALLET FORK) | 2,558 LBS                               | 2,933 LBS                               |
| WORKING HYDRAULICS             | 10.3 GPM<br>9.8 GPM - CONSTANT FLOW OPT | 10.3 GPM<br>9.8 GPM - CONSTANT FLOW OPT |
| MAX SPEED                      | 12.4 MPH                                | 12.4 MPH                                |
| WIDTH                          | 43-50 IN                                | 43-50 IN                                |



COMPACT DESIGN, **BIG PERFORMANCE** | [www.giantloaders.com](http://www.giantloaders.com)  
319.449.3677 | [info@giantloaders.com](mailto:info@giantloaders.com)



\*INFORMATION IS SUBJECT TO CHANGE

# G2300HD SERIES COMPACT WHEEL LOADER



## DIMENSIONS

|          | G2300HD                           | G2300HD X-TRA                     |
|----------|-----------------------------------|-----------------------------------|
| <b>A</b> | 60.2 in                           | 62.2 in                           |
| <b>B</b> | 126.6 in                          | 128.3 in                          |
| <b>C</b> | 157.9 in                          | 159.1 in                          |
| <b>D</b> | 89.8 in (Cabin)                   | 89.8 in (Cabin)                   |
| <b>E</b> | 90.6 in<br>(canopy/foldable roof) | 90.6 in<br>(canopy/foldable roof) |
| <b>F</b> | 58.3 in                           | 49.2 in                           |
| <b>G</b> | 78.3 in                           | 66.1 in                           |
| <b>H</b> | 111.4 in                          | 96.5 in                           |
| <b>I</b> | 133.5 in                          | 119.7 in                          |
| <b>J</b> | 43°                               | 41°                               |
| <b>K</b> | 53°                               | 46°                               |
| <b>L</b> | 47°                               | 37°                               |
| <b>M</b> | Ø29.9 in                          | Ø29.9 in                          |
| <b>N</b> | 26°                               | 26°                               |
| <b>O</b> | 29.4 in                           | 31.5 in                           |
| <b>P</b> | 30.6 in                           | 30.6 in                           |



Less tire wear and ground damage



Enhanced operator comfort through articulation and oscillation



Bridging the gap between skid steers and large wheel loaders



Safe and ergonomic operator station with side entry



Higher lift heights and tipping loads compared to service weight

